

**METHOD AND APPARATUS FOR IMPROVING
THE EFFICIENCY OF A COMBUSTION DEVICE**

The present invention relates to improving the efficiency of a combustion device by optimizing the concentration or amount of a combustion characteristic in the combusted gas. In another aspect, the invention relates to a method and apparatus for improving the efficiency of a combustion device by adjusting the flow of air to burners contained in the combustion device in response to a measured combustion characteristic of the combusted gas.

Background of the Invention

Combustion devices such as furnaces, boilers, ovens, or stoves are devices in which heat energy is transferred to a charge or feed in a controlled manner. The typical combustion device takes the form of a metal housing lined with heat-conserving refractory. The charge or feed can enter as a solid, liquid or gas and may or may not be transformed to a different state. The charge or feed

can be carried through the combustion device continuously through metal tubes or troughs or may be batch-heated. The functions of combustion devices include, but are not limited to, 1) heating or vaporizing the charge; 2) providing heat of reaction to reacting feeds (such as in a cracking reaction) and 3) providing an elevated and controlled temperature for the physical change of charge materials.

An example of a combustion device is a hydrocarbon cracking furnace which transfers heat in a controlled manner to a hydrocarbon, such as ethane, propane or butane, for conversion to olefins. The typical air flow burner adjustment method for such furnaces is based on furnace draft measurements, flame appearance and volume percent oxygen in the stack outlet gas. This procedure can lead to inefficient furnace operation wherein the oxygen level in the stack outlet gas is low, but the heat used for high economic value processes is also low. This can occur if significant fuel combustion and heat transfer occurs in the secondary heat recovery section, higher in the furnace (nearer the stack) and not in the lower section of the furnace where the highest economic value can be realized from the heat transferred to the charge materials.

Thus, it would be clearly desirable to provide a method and/or apparatus for controlling the operation of a combustion device which results in more efficient operation of the combustion device through maximizing heat transfer to charge materials.

Summary of the Invention

It is an object of the present invention to provide a method of optimizing the efficiency of a combustion device.

A further object of this invention is to provide an apparatus to be used for optimizing the efficiency of a combustion device.

It is yet another object of this invention to provide a method and/or apparatus for optimizing the efficiency of a furnace by maintaining the concentration of a combustion characteristic of the combusted gas, from at least one burner assembly contained therein, within a predetermined range by adjusting the flow of air to at least one burner assembly in response to measured combustion characteristic concentrations.

According to a first embodiment of the present invention, a method of optimizing the efficiency of a combustion device comprising at least one control zone, with each control zone comprising at least one burner assembly, is provided and comprises the steps of:

a) individually supplying fuel to each of the burner assemblies in each of the control zones;

b) individually measuring a combustion characteristic of the collective combusted gas from the burner assemblies in each of the control zones; and

c) individually adjusting the flow of air to each of the burner assemblies in each of the control zones in response to the value of the combustion characteristic corresponding to each of the control zones to keep the value of each of the combustion characteristics within a predetermined range.

5 According to a second embodiment of the present invention, a method of optimizing the efficiency of a combustion device comprising at least one control zone, with each control zone comprising at least one burner assembly, is provided and includes the steps of:

a) individually supplying fuel to each of the burner assemblies in each of the control zones;

b) individually supplying primary air to each of the burner assemblies in each of the control zones for mixture and at least partial combustion with the fuel supplied thereto thereby producing a separate intermediate combustion product for each of the burner assemblies;

15 c) individually supplying secondary air to each of the burner assemblies in each of the control zones for mixture with the intermediate combustion product for further combustion thereby producing a combusted gas stream for each of the plurality of burner assemblies;

d) individually measuring a combustion characteristic of the collective combusted gas from the burner assemblies in each of the control zones; and

e) individually adjusting the flow of primary air and individually adjusting the flow of secondary air to each of the burner assemblies in each of the control zones in response to the value of the combustion characteristic corresponding to each of the control zones to keep the value of each of the combustion characteristics within a predetermined range.

According to a third embodiment of the present invention, a combustion device is provided comprising:

a) at least one control zone comprising at least one burner assembly;

b) at least one gas analyzer operably related to each of the control zones for receiving and analyzing samples of combusted gas from the control zones;

c) each of the burner assemblies comprising:

i) a fuel introduction means for introducing fuel into the burner assembly;

ii) a primary air introduction means for introducing primary air into the burner assembly for mixture and at least partial combustion with the fuel, thereby producing an intermediate combustion product; and

iii) a secondary air introduction means for introducing secondary air into the burner assembly for mixture and further combustion with the

intermediate combustion product, thereby producing a combusted gas stream for each of the burner assemblies; and

d) control means operably related to the primary air introduction means, the secondary air introduction means, and the at least one gas analyzer, for adjusting the flow of primary air and the flow of secondary air to each of the burner assemblies in each of the control zones through the primary air introduction means and the secondary air introduction means, respectively, in response to the value of a combustion characteristic measured in the collective combusted gas streams corresponding to each of the control zones.

Other objects and advantages will become apparent from the detailed description and the appended claims.

Brief Description of the Drawings

Figure 1 is a schematic diagram of a combustion device constructed in accordance with the present invention.

Figure 2 is a schematic diagram showing in greater detail certain features of the combustion device shown in Figure 1.

Figure 3 is a schematic diagram of a combusted gas sampling cart constructed in accordance with the present invention.

Detailed Description of the Invention

Combustion devices suitable for optimization in the present invention include, but are not limited to, a furnace, a boiler, an oven, or a stove.

In accordance with the first embodiment of the present invention, a method of optimizing the efficiency of a combustion device comprising at least one control zone, with each control zone comprising at least one burner assembly, comprises, consists of, or consists essentially of the following.

5 Individually supplying fuel to each of the burner assemblies. The fuel can be any fuel suitable for supplying heat to a furnace upon combustion, including liquid and gaseous fuels. Most typically, the fuel is a gaseous hydrocarbon such as, but not limited to, natural gas or hydrogen, or the like, and combinations of such fuels. The fuel is burned, in the presence of air, to form
10 combusted gas corresponding to each of the burner assemblies. A separate combustion characteristic of the collective combusted gas from the burner assemblies in each of the control zones is individually measured for each control zone. The measurement is made by any suitable method capable of measuring the combustion characteristic, and is most preferably measured using a gas analyzer,
15 which can include, but is not limited to include, an electrolytic cell and/or a non-dispersive infrared (NDIR) analyzer. The flow of air to each of the burner assemblies in each of the control zones is individually adjusted in response to the value of the combustion characteristic corresponding to each of the control zones to keep the value of each separate combustion characteristic within a
20 predetermined range.

The combustion characteristic can comprise, consist of, or consist essentially of a component selected from the group consisting of oxygen concentration, carbon monoxide concentration, carbon dioxide concentration, and combinations thereof.

5 The predetermined range for the combustion characteristic, when it is oxygen concentration, is in the range of from about 0.5 to about 5.0 volume %, preferably from about 1.0 to about 3.0 volume %, and most preferably from 1.5 to 2.0 volume %, based on the total volume of the collective combusted gas for each of the control zones.

10 The predetermined range for the combustion characteristic, when it is carbon monoxide concentration, is preferably less than about 1000 ppmv, more preferably less than about 500 ppmv, and most preferably substantially 0 ppmv, based on the total volume of the collective combusted gas for each of the control zones.

15 The predetermined range for the combustion characteristic, when it is carbon dioxide concentration, is preferably greater than about 2.0 volume %, more preferably greater than about 5.0 volume %, and most preferably greater than 10.0 volume %, based on the total volume of the collective combusted gas for each of the control zones.

20 In accordance with the second embodiment of the present invention, a method of optimizing the efficiency of a combustion device

comprising at least one control zone, with each of the control zones comprising at least one burner assembly, includes the following.

Fuel, such as the fuel described above, is individually supplied to each of the burner assemblies in each of the control zones. Primary air is individually supplied to each of the burner assemblies in each of the control zones for mixture and at least partial combustion with the fuel supplied thereto, thereby producing a separate intermediate combustion product for each of the burner assemblies. The intermediate combustion product can contain non-combusted fuel or partially combusted fuel.

Secondary air can also be individually supplied to each of the burner assemblies in each of the control zones for mixture with the intermediate combustion product for further combustion with any non-combusted fuel contained in the intermediate combustion product, thereby producing a combusted gas stream for each of the burner assemblies. The combusted gas stream generally contains substantially less non-combusted fuel as compared to the fuel stream, and is preferably substantially free of non-combusted fuel.

A combustion characteristic, as described above, of the combusted gas is individually measured for the collective combusted gas from the burner assemblies in each of the control zones. The flow of primary air and the flow of secondary air to each of the burner assemblies in each of the control zones is individually adjusted in response to the value of the combustion characteristic

corresponding to each of the control zones in order to keep the value of each separate combustion characteristic within the predetermined ranges set out above in the first embodiment.

Preferably, the flow of primary air to each of the burner assemblies is adjusted in response to the value of the combustion characteristic corresponding to each of the control zones first, followed by adjustment of the flow of secondary air, as needed, in order to keep the value of each combustion characteristic within the above described predetermined range.

In accordance with the third embodiment of the present invention, and referring to Fig. 1, therein is illustrated combustion device 10 having an inside wall 12 and including at least one control zone 14. Each of the control zones 14 contain at least one burner assembly 16 disposed along the length of inside wall 12. The combustion device 10 also includes at least one gas analyzer 18 having at least one probe 20 operably related to the control zones 14 for receiving and analyzing samples of combusted gas from control zones 14.

Referring to Fig. 2 for further description of the burner assemblies 16, each of the burner assemblies comprises a first mix chamber 22, a second mix chamber 24, a fuel introduction means 26 for introducing fuel to first mix chamber 22, an adjustable primary air register 28 providing primary air introduction means for introducing primary air 30 into first mix chamber 22. The primary air mixes with the fuel for combustion thereby producing an

intermediate combustion product delivered to second mix chamber 24 via introduction means 32, which is connected in fluid flow communication with first mix chamber 22 and with second mix chamber 24. Burner assembly 16 also comprises an adjustable secondary air register 34 providing secondary air introduction means for introducing secondary air 36 into the second mix chamber 24 for mixture and further combustion with the intermediate combustion product thereby producing a combusted gas stream 38 for each burner assembly 16. The adjustable primary and secondary air registers, 28 and 34, respectively, are configured such that they can be opened or closed to allow more or less air to pass into burner assembly 16.

In addition, the inventive combustion device 10 can include a control system operably related to adjustable primary air register 28, adjustable secondary air register 34, and gas analyzer 18 which provides control means for adjusting the flow of primary air and the flow of secondary air to each of the burner assemblies 16 in each of the control zones 14 through adjustable primary air register 28 and adjustable secondary air register 34, respectively, in response to the value of a combustion characteristic measured in the collective combusted gas streams 38 corresponding to each of the control zones 14.

Dash lines, which designate signal lines in the drawings, are electrical or pneumatic in this preferred embodiment. However, the invention is also applicable to mechanical, hydraulic, or other signal means for transmitting

information. In almost all control systems some combination of these types of signals will be used. However, the use of any other type of signal transmission, compatible with the process and equipment in use, is within the scope of the invention.

5 A digital computer is used in the preferred embodiment of this invention to calculate the required control signals based on measured process parameters as well as set points supplied to the computer. Any computer control system having software that allows operation in a real time environment for reading values of external variables and transmitting signals is suitable for use in this invention.

10 Signal lines are also utilized to represent the results of calculations carried out in a digital computer and the term "signal" is utilized to refer to such results. Thus, the term signal is used not only to refer to electrical currents or pneumatic pressures but is also used to refer to binary representations of a calculated or measured value.

15 The controllers shown may utilize the various modes of control such as proportional, proportional-integral, proportional-derivative, proportional-integral-derivative, or model predictive. In this preferred embodiment, proportional-integral-derivative controllers are utilized but any controller capable of accepting two input signals and producing a scaled output

20

signal, representative of a comparison of the two input signals, is within the scope of the invention.

The scaling of an output signal by a controller is well known in control system art. Essentially, the output of a controller may be scaled to represent any desired factor or variable. An example of this is where a desired flow rate and an actual flow rate are compared by a controller. The output could be a signal representative of a desired change in the flow rate of some liquid necessary to make the desired and actual flows equal. On the other hand, the same output signal could be scaled to represent a percentage or could be scaled to represent a temperature change required to make the desired and actual flows equal, or could be scaled to represent the position of a mechanical device. If the controller output can range from 0 to 10 volts, which is typical, then the output signal could be scaled so that an output signal having a voltage level of 5.0 volts corresponds to 50 percent of some specified flow rate, or could be scaled so that an output signal having a voltage level of 5.0 volts corresponds to positioning a mechanical device to a 50% open position, such as an adjustable air register.

The various transducing means used to measure parameters which characterize the process and the various signals generated thereby may take a variety of forms or formats. For example, the control elements of the system can be implemented using electrical analog, digital electronic, pneumatic, hydraulic, mechanical or other similar types of equipment or combinations of

one or more such equipment types. While the presently preferred embodiment of the invention preferably utilizes a combination of pneumatic final control elements in conjunction with electrical analog signal handling and translation apparatus, the apparatus and method of the invention can be implemented using a variety of specific equipment available to and understood by those skilled in the process control art.

Likewise, the format of the various signals can be modified substantially in order to accommodate signal format requirements of the particular installation, safety factors, the physical characteristics of the measuring or control instruments and other similar factors. For example, a raw flow measurement signal produced by a differential pressure orifice flow meter would ordinarily exhibit a generally proportional relationship to the square of the actual flow rate. Other measuring instruments might produce a signal which is proportional to the measured parameter, and still other transducing means may produce a signal which bears a more complicated, but known, relationship to the measured parameter.

Regardless of the signal format or the exact relationship of the signal to the parameter which it represents, each signal representative of a measured process parameter or representative of a desired process value or representative of the position of a mechanical device will bear a relationship to the measured parameter or desired value or position which permits designation

of a specific measured or desired value or position by a specific signal value. A signal which is representative of a process measurement or desired process value is therefore one from which the information regarding the measured or desired value can be readily retrieved regardless of the exact mathematical relationship between the signal units and the measured or desired process units.

Referring again to Fig. 2, the control system can be described as follows.

Adjustable primary air register 28 is operably related to a first register controller 40 for adjusting the register position. Adjustable secondary air register 34 is operably related to a second register controller 42 for adjusting the register position.

Gas analyzer 18 provides means for establishing a signal 44 representative of the actual value of a combustion characteristic of the combined combusted gas streams 38 measured by gas analyzer 18. Gas analyzer 18 is adapted to deliver, in response to the analysis of the combined combusted gas streams, signal 44.

A computer calculation block 46, providing computer means and preferably associated with a distributed control system, receives as inputs thereto combustion characteristic signal 44 and an operator entered signal 48 which is a set point representative of the desired value of the combustion characteristic.

Computer calculation block 46 establishes output signals 50 and 52, each responsive to the difference between signals 44 and 48. Signals 50 and 52 are scaled to be representative of the air register positions of the adjustable primary air register 28 and the adjustable secondary air register 34, respectively, required to maintain the actual value of the combustion characteristic represented by signal 44 substantially equal to the desired value of the combustion characteristic represented by signal 48.

Signal 50 is provided as a set-point to first register controller 40 for positioning of adjustable primary air register 28 accordingly.

Signal 52 is provided as a set point to second register controller 42 for positioning of adjustable secondary air register 34 accordingly.

The inventive combustion device 10 can be operated by:

- a) providing the combustion device described above;
- b) introducing fuel into each of the burner assemblies 16 in each of the control zones via the fuel introduction means 26;
- c) introducing primary air into the first mix chamber 22 of the burner assemblies 16 in the control zones 14 via the primary air introduction means 28 for mixture and combustion with the fuel thereby producing an intermediate combustion product;
- d) introducing secondary air into the second mix chamber 24 of the burner assemblies 16 in the control zones 14 via the secondary air

introduction means 34 for mixture and further combustion with the intermediate combustion product delivered by introduction means 32 thereby producing a combusted gas stream 38 for each of the burner assemblies 16;

e) individually measuring the value of the combustion characteristic in the collective combusted gas streams 38 corresponding to each of the control zones 14; and

f) adjusting the flow of primary air and the flow of secondary air to each of the burner assemblies 16 in each of the control zones 14 through the primary air introduction means 28 and the secondary air introduction means 34, respectively, in response to the value of the combustion characteristic measured in step e) corresponding to each of the control zones 14.

Preferably, the flow of primary air to each of the burner assemblies 16 in the plurality of control zones 14 is adjusted via the control means in response to the value of the combustion characteristic corresponding to each of the control zones 14 first, followed by adjustment of the flow of the secondary air, as needed, via the control means in order to keep the value of each combustion characteristic within a predetermined range.

The adjustment of the flow of primary air and the flow of secondary air to each of the burner assemblies 16 of step f) is performed such that the oxygen concentration in the collective combusted gas 38 for each of the control zones 14 is in the range of from about 0.5 to about 5.0 volume %,

preferably from about 1.0 to about 3.0, and most preferably from 1.5 to 2.0, based on the total volume of the collective combusted gas, and/or such that carbon monoxide concentration in the collective combusted gas for each of the control zones 14 is preferably less than 1000 ppmv, more preferably less than about 500 ppmv, and most preferably substantially 0 ppmv, and/or such that carbon dioxide concentration in the collective combusted gas for each of the control zones 14 is preferably greater than about 2.0 volume %, more preferably greater than about 5.0 volume %, and most preferably greater than 10.0 volume %, based on the total volume of the collective combusted gas 38.

Referring to Figure 3, and in accordance with the invention, therein is illustrated an apparatus 50 suitable for analyzing combusted gas from a combustion device including a moveable cart 52 physically supporting the components described hereafter. A combusted gas probe 54, which can be water cooled, is connected in fluid flow communication via conduit 56 with a free water knock-out vessel 58, conduit 56 being suitable for delivering a combusted gas stream to free water knock-out vessel 58. Free water knock-out vessel 58 includes a conduit 60, having a valve 62 disposed therein, suitable for removing free water from free water knock-out vessel 58 which is separated from the combusted gas stream. Free water knock-out vessel 58 is also connected in fluid flow communication via conduit 64 with a vacuum pump 66 which provides motive force to the combusted gas stream. Vacuum pump 66 is connected in

fluid flow communication via conduit 68 to a condenser 70 contained (submerged) in a cooler 72 for condensation of condensibles, such as water. The cooler 72 can be an ice bath.

Condenser 70 is connected in fluid flow communication via conduit 74 with a condensed water knock-out vessel 76 contained in cooler 72. Condensed water knock-out vessel 76 includes a conduit 78 having a valve 80 disposed therein suitable for removing condensed condensibles from condensed water knock-out vessel 76 which are separated from the combusted gas stream.

Condensed water knock-out vessel 76 is connected in fluid flow communication via conduit 82 with a combusted gas analyzer 84 wherein the combusted gas stream is analyzed for a combustion characteristic and the analysis results are displayed by paper printout or on a computer display terminal for operator use in adjusting primary and/or secondary air registers.

The inventive apparatus described above can be operated by:

a) supplying the apparatus described above; b) introducing a combusted gas stream from a combustion device to the free water knock-out vessel 58 via the combusted gas probe 54 and conduit 56; c) permitting free water in the combusted gas stream to separate from the combusted gas stream for removal from the free water knock-out vessel 58 via conduit 60; d) passing the combusted gas stream to the vacuum pump 66 via conduit 64; e) passing the combusted gas stream to the condenser 70 of the cooler 72 for condensation of

at least a portion of the combusted gas stream thereby forming a liquid phase and a gas phase which are passed to the condensed water knock-out vessel 76 via conduit 74 for separation; and f) removing the liquid phase from the condensed water knock-out vessel 76 and passing the gas phase to the combusted gas analyzer 84 via conduit 82 for analysis.

Example

The inventive method was tested on two commercial ethylene furnaces hereinafter referred to as Furnace A and Furnace B. These two furnaces produce ethylene, propylene, and other products by pyrolyzing a mixture of ethane and propane. They are large and consume vast quantities of fuel, so even small changes in their overall efficiency result in significant cost savings. The test consisted of three surveys of the two furnaces over the period of one calendar year. The first two surveys were primarily devoted to developing the measurement procedure and documenting the need for an improved burner adjustment method. The third survey was used to demonstrate the efficacy of the inventive adjustment method.

The burners of Furnace A and Furnace B are fueled by a mixture of hydrogen and methane with small amounts of other hydrocarbons. Air for combustion is supplied to each burner through two sets of air registers. The

primary air registers provide air that is mixed with the fuel prior to combustion and the secondary registers provide air that is mixed with the fuel and primary air during and after combustion.

Proper adjustment of the burner air registers is vital in induced-draft furnaces such as Furnace A and Furnace B. Heat transfer to the pyrolysis tubes is highly dependent upon the size, shape, and intensity of the flames, all of which are directly affected by the amount of primary and secondary air that the burner receives. Since the furnaces are tall and contain many rows of burners, the vertical profile of the burners and their flames must also be considered and adjusted properly.

The standard method for adjusting the burner air registers to achieve optimum combustion conditions is based upon furnace draft and the appearance of the flames. The burner vendors taught maintenance personnel to adjust the burners on Furnace A and Furnace B in accordance with the standard method. The inventors believed the standard method to be flawed because draft is not necessarily linked to flame stoichiometry. Furthermore, the appearance of the typical high-hydrogen fuel flame gives no information about flame stoichiometry.

Survey and Testing Procedure

Combustion gas samples were collected using water-cooled steel probes which were inserted through peep doors into the furnaces. A piece of

fabric insulation was used to seal around the probe and prevent air leaks into the furnaces through the peep doors during sampling. The sampled gases were analyzed in real-time using a Horiba MEXA-554J gas analyzer utilizing an electrolytic cell for O₂ measurement and non dispersive IR for CO and CO₂ measurement.

First Survey

Furnace A had been adjusted according to the vendor-recommended procedure prior to the first survey and was believed to be running well. However, the inventors' measurements (Table 1) showed that CO was present throughout the radiant section, a sure indication that the burners were not receiving enough oxygen. Since stack CO remained low, it was evident that final burning was occurring in the convection section.

Table 1				
First Survey - Furnace A				
Location	CO (ppmv)	CO ₂ (vol. %)	O ₂ (vol. %)	SR ²
Convection Section	0.0	10.0	1.0	1.05
Radiant Section Level ¹ 4	Not Surveyed			
3	3.4	8.5	0.0	0.93
2	Not Surveyed			
1	1.5	9.6	0.0	0.97
1 - Furnace A has 4 radiant section levels. 2 - SR - Stoichiometric Ratio of Oxygen to fuel. A SR of 1.0 represents complete combustion.				

Subsequent to the first survey, the operators opened the air registers on six of the furnaces in the plant, including Furnace A and Furnace B, to provide more air to the furnaces. Their adjustments succeeded in adding more fuel capacity to most, but not all, of the furnaces.

Second Survey

The second survey was conducted about three months after the first survey. By that time, the furnaces had again been adjusted according to the vendor-recommended procedure. The findings of the second survey are presented in Table 2. The concentration of oxygen ranged from 5.8% at the bottom to 2.2% in the convection section. The 2.2% oxygen concentration in the convection section would lead to similar stack oxygen concentrations from which operators would conclude that the furnace was running well. However, the high levels of oxygen lower in the furnace instead indicate that the furnace was in fact seriously unbalanced. While the overall amount of air entering the furnace was appropriate, the air was maldistributed. Too much air was entering at the lower burners and too little was entering at the higher burners. The excess air near the lower burners necessarily caused lower flame temperatures and reduced heat flux to the pyrolysis coils. The inventors also noted that the primary air registers on the lowest row of burners were completely closed, and consequently, believed the burners were operating diffusion flames rather than the preferred premixed flames. The surplus air from the lower part of the

furnace rises to the upper rows of burners where it mixes with uncombusted fuel. The resulting diffusion flames are not very intense and therefore transfer heat to the pyrolysis coils poorly. Clearly, it is evident that Furnace A had been switched from the oxygen-deprived conditions observed during the first survey to oxygen-rich conditions but draft and flame appearance had again failed to optimize operations.

Table 2				
Second Survey - Furnace A				
Location	CO (ppmv)	CO ₂ (vol. %)	O ₂ (vol. %)	SR ²
Convection Section	0.005	9.6	2.2	1.1
Radiant Section Level ¹ 4	Not Surveyed			
3	0	9.6	3.0	1.2
2	Not Surveyed			
1	0	7.8	5.8	1.3
1 - Furnace A has 4 radiant section levels. 2 - SR - Stoichiometric Ratio of Oxygen to fuel. A SR of 1.0 represents complete combustion.				

Third Survey

The inventive cart was designed and fashioned following the second survey to make moving from one location to another on the furnaces quicker and to speed the analysis. With the cart, a furnace could be sampled in less than an hour. Thus Furnace A and Furnace B were sampled multiple times

during the third survey whereas three days had been required to sample Furnace A alone on the second survey. The manpower required to complete a survey was also reduced from three men to two with the cart.

The third survey was carried out about three months after the second survey and was for the purpose of bringing Furnaces A and B as close as possible to optimal performance. An initial sampling of Furnace A (see Table 3) confirmed that the conditions observed on the second survey, namely an excess of air on the bottom and a shortage of air near the top row of burners, still existed. The primary air registers on the bottom row of burners remained closed.

Table 3				
Third Survey - Furnace A-Initial				
Location	CO (ppmv)	CO ₂ (vol. %)	O ₂ (vol. %)	SR ²
Convection Section				
Radiant Section Level ¹ 4				
3				
2	0	7.4	6.1	1.4
1	0	7.4	6.2	1.4
¹ - Furnace A has 4 radiant section levels. ² - SR - Stoichiometric Ratio of Oxygen to fuel. A SR of 1.0 represents complete combustion.				

Adjustments began by opening the secondary registers on the two uppermost levels of burners of Furnace A. Then the primary registers on the

bottom row of burners were opened. In-furnace measurement with the inventive cart indicated that these actions lowered the oxygen concentration at the lowest level of the furnace to 3.4%. Since less air then flowed into the lower part of the furnace, more air flowed elsewhere. This was reflected in the stack oxygen sensor, which showed that more oxygen was available. Consequently, the operator began to add more charge. As the charge increased, the automatic fuel flow controllers added more fuel, which consumed the additional oxygen. Additional probe measurements of oxygen and carbon monoxide concentration showed that the primary air registers on the bottom row of burners were providing insufficient air, so the secondary air registers were opened partially. The primary air registers at the top of the furnace were then opened. While these adjustments were occurring, the operator continued to add charge as the stack sensor showed additional oxygen available. A cycle of opening air registers, observing free oxygen, adding charge, and then waiting several hours for the furnace to equilibrate was established. The final probe measurements in Furnace A are presented in Table 4.

Table 4			
Final survey - Furnace A			
Location:	CO (ppmv)	CO2 (vol. %)	O2 (vol. %)
Radiant Section Level ¹			
4	.05	9.4	1.9
3	0	9.2	2.5
2	0	8.9	3.2
1	N/a	N/a	N/a
1 - Furnace A has 4 radiant section levels. N/a - Not analyzed			

The effect of the air register adjustments on the operation of Furnace A is summarized in Table 5. The key result is that the charge to the furnace increased by 11% while the fuel mass flow rate (not shown in Table 5) increased only by 9%. This means that the inventively adjusted furnace is processing more charge at a lower marginal cost as compared to the industry standard adjustment method. The production of steam, a by-product, increased in proportion to the charge. Also, the amount of oxygen in the stack decreased from 2.8% to 1.5%, indicating that the amount of air being drawn through the furnace is closer to the stoichiometric amount than before.

Table 5			
Impact of Inventive Adjustment Procedure on Furnace A Operation			
	Before	After	Change
Charge (lb/hr/coil)	6500	7200	11%
Excess O ₂ (mole %)	2.8	1.5	
Steam Produced (klb/hr)	107	118	11%

Following the completion of work on Furnace A, a survey of Furnace B was performed. The results of that survey (see Table 6) indicate that Furnace B (adjusted per the industry standard method) operations were very similar to Furnace A, with relatively high oxygen concentrations throughout.

Table 6			
Initial Survey - Furnace B			
Location:	CO (ppmv)	CO ₂ (vol. %)	O ₂ (vol. %)
Radiant Section Level ¹			
4	.06	7.4	5.8
3	0.1	7.6	5.4
2	0	7.2	6.6
1	0	6	8.8
1 - Furnace B has 4 radiant section levels.			

An air register adjustment and charge increase procedure similar to that used on Furnace A was then followed. The final in-furnace measurements are presented in Table 7.

Table 7			
Final Survey - Furnace B			
Location:	CO (ppmv)	CO ₂ (vol. %)	O ₂ (vol. %)
Radiant Section Level ¹			
4	.04	8.2	3.6
3	0	8.0	4.8
2	0	7.4	5.6
1	0	7.3	6.1
1 - Furnace B has 4 radiant section levels.			

Furnace operation results are presented in Table 8.

Table 8			
Impact of Inventive Adjustment Procedure on Furnace B Operation			
	Before	After	Change
Charge (lb/hr/coil)	5900	6400	8%
Excess O ₂ (mole %)	1.8	1.6	
Steam Produced (klb/hr)	82	90	9%

The charge to Furnace B increased 8% while the fuel mass flow rate (not shown in Table 8) only increased 2%. Steam production increased and crossover temperature, an operating parameter, remained unchanged.

It should be noted that the oxygen readings were thought to be somewhat higher than actual during the survey of Furnace B due to the lack of a sealing gasket on the analyzer that was lost sometime during the day. Therefore,

the reported oxygen data for Furnace B are less certain than for Furnace A, but the operation data provide strong evidence that similar results were obtained, and that the inventive adjustment procedure resulted in more efficient furnace operation as compared to the industry standard adjustment procedure.

5 The long-term sustainability of the increased charge rates could not be determined because the unit (including furnaces A and B) was forced to cut charge immediately after the surveying and adjusting were finished in order to process offtest ethylene from other units.

10 A portion of the fuel capacity increase observed during the third survey appears to be due to the fact that the adjustments resulted in more air being supplied to furnaces A and B. However, it is important to note that the air was redistributed as well. By increasing the proportions of primary air, which were particularly low in the furnace prior to implementation of the inventive method, it is believed that the burners' heat transfer efficiency was increased.

15 Also, without the use of the inventive method, none of the adjustments would have been made because the furnaces were believed to be optimized based on furnace draft data and flame appearance.

Thus, the results described in the above example demonstrate that use of the inventive method and/or apparatus for operating a combustion device results in improved operation and efficiency as compared to combustion device operation without use of the inventive method and/or apparatus.

5

Whereas this invention has been described in terms of the preferred embodiments, reasonable variations and modifications are possible by those skilled in the art. Such modifications are within the scope of the described invention and appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204